

5800



FUEL, STABILIZER, UNIT RESCUE-8 : 09/27/2001 :

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 001  
Date Prepared: 02/10/95  
Date Printed: 11/06/99  
MSDS No: 503.0244693-001.008

### FUEL STABILIZER

---

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### Material Identity

Product Name: FUEL STABILIZER  
Product Code: 00005800  
General or Generic ID: AUTOMOTIVE CHEMICAL

### Company

The Valvoline Company  
P.O. Box 14000  
Lexington, KY 40512

### Telephone Numbers

Emergency: 1-800-274-5263  
Information: 1-606-357-7847

---

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
KEROSENE	8008-20-6	91.0-100.0
BUTYLATED HYDROXYTOLUENE	128-37-0	0.0- 8.0

---

## 3. HAZARDS IDENTIFICATION

### Potential Health Effects

#### Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

#### Skin

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

#### Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

#### Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

#### Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

#### Target Organ Effects

No data

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002  
Date Prepared: 02/10/95  
Date Printed: 11/06/99  
MSDS No: 503.0244693-001.008

### FUEL STABILIZER

---

#### Developmental Information

No data

#### Cancer Information

No data

#### Other Health Effects

No data

#### Primary Route(s) of Entry

Inhalation, Skin contact.

---

### 4. FIRST AID MEASURES

#### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

#### Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

#### Swallowing

Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

#### Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

#### Note to Physicians

No data

---

### 5. FIRE FIGHTING MEASURES

#### Flash Point

> 120.0 F (48.8 C)

#### Explosive Limit

(for component) Lower .7 %

#### Autoignition Temperature

No data

#### Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003  
Date Prepared: 02/10/95  
Date Printed: 11/06/99  
MSDS No: 503.0244693-001.008

### FUEL STABILIZER

---

#### Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

#### Extinguishing Media

regular foam, carbon dioxide, dry chemical.

#### Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

#### NFPA Rating

Health - 1, Flammability - 2, Reactivity - 0

---

### 6. ACCIDENTAL RELEASE MEASURES

#### Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

#### Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

---

### 7. HANDLING AND STORAGE

#### Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

#### Storage

Not applicable

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004  
Date Prepared: 02/10/95  
Date Printed: 11/06/99  
MSDS No: 503.0244693-001.008

### FUEL STABILIZER

---

#### Skin Protection

Wear resistant gloves such as: neoprene, nitrile rubber, To prevent repeated or prolonged skin contact, wear impervious clothing and boots..

#### Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

#### Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

#### Exposure Guidelines

Component  
-----

KEROSENE (8008-20-6)  
No exposure limits established

BUTYLATED HYDROXYTOLUENE (128-37-0)  
OSHA VPEL 10.000 mg/m<sup>3</sup> - TWA  
ACGIH TLV 10.000 mg/m<sup>3</sup> - TWA

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Boiling Point

(for component) > 300.0 F (148.8 C) @ 760.00 mmHg

#### Vapor Pressure

(for component) 5.000 mmHg @ 77.00 F

#### Specific Vapor Density

> 1.000 @ AIR=1

#### Specific Gravity

.797 - .820 @ 77.00 F

#### Liquid Density

6.740 lbs/gal @ 77.00 F  
.809 kg/l @ 25.00 C

#### Percent Volatiles (Including Water)

> 95.0 %

#### Evaporation Rate

SLOWER THAN ETHYL ETHER

#### Appearance

CLEAR

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005  
Date Prepared: 02/10/95  
Date Printed: 11/06/99  
MSDS No: 503.0244693-001.008

### FUEL STABILIZER

---

**State**

LIQUID

**Physical Form**

No data

**Color**

YELLOW

**Odor**

No data

**pH**

Not applicable

---

### 10. STABILITY AND REACTIVITY

**Hazardous Polymerization**

Product will not undergo hazardous polymerization.

**Hazardous Decomposition**

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**Chemical Stability**

Stable.

**Incompatibility**

Avoid contact with: strong oxidizing agents.

---

### 11. TOXICOLOGICAL INFORMATION

No data

---

### 12. ECOLOGICAL INFORMATION

No data

---

### 13. DISPOSAL CONSIDERATION

**Waste Management Information**

Destroy by liquid incineration. Dispose of in accordance with all applicable local, state and federal regulations.

---

### 14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

Not Regulated

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006  
Date Prepared: 02/10/95  
Date Printed: 11/06/99  
MSDS No: 503.0244693-001.008

### FUEL STABILIZER

---

**Container/Mode:**  
CASES/SURFACE - COMBUSTIBLE EXCEPTION

**NOS Component:**  
KEROSENE

**RQ (Reportable Quantity) - 49 CFR 172.101**  
Product Quantity (lbs) Component

-----  
29121 XYLENES (O-, M-, P- ISOMERS)

---

### 15. REGULATORY INFORMATION

#### US Federal Regulations

**TSCA (Toxic Substances Control Act) Status**  
TSCA (UNITED STATES) The intentional ingredients of this product are listed.

**CERCLA RQ - 40 CFR 302.4**  
None

**SARA 302 Components - 40 CFR 355 Appendix A**  
None

**Section 311/312 Hazard Class - 40 CFR 370.2**  
Immediate(X) Delayed( ) Fire( ) Reactive( ) Sudden Release of  
Pressure( )

**SARA 313 Components - 40 CFR 372.65**  
None

#### International Regulations

**Inventory Status**  
Not determined

#### State and Local Regulations

**California Proposition 65**  
None

#### New Jersey RTK Label Information

KEROSENE 8008-20-6  
2,6-DI-TERT-BUTYL-P-CRESOL 128-37-0

#### Pennsylvania RTK Label Information

KEROSINE (PETROLEUM) 8008-20-6  
PHENOL, 2,6-BIS(1,1-DIMETHYLETHYL)-4-MET 128-37-0

---

### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.